

# VON DUPRIN®

## 237 Two Point Latch

The 237 Two-Point Latch Assembly is ideal for spaces where occupancy does not require panic or fire exit hardware. This product is a perfect solution for many applications in schools, health care facilities, offices, and government facilities - regardless if the doors are inswing or outswing. It can be used on the inactive leaf of a pair of doors with a lockset or both leaves of a pair. It features a top soffitt latch and ratchet release for long service life and dependability. Locking handles in many different configurations provide versatility to meet different customer needs.

Engineered to withstand severe weather conditions, the 237 series is also ideal for community shelters and safe rooms in accordance with FEMA 320 and 361 guidelines.

### Specifications Compliance

#### I. UL Listings:

Two-and Three-point Locks and Latches (for use on Fire Doors) – UL 10 C

Rating: 3HR Pairs (Double Egress)

90 Min. Pairs (Swing Same Direction)

Door Size: 8'0 x 8'0 Pairs (Hollow Metal only)

#### II. Windstorm Ratings:

A. UL – FEMA 320 and 361 certified:

i. 4'0 x 8'0 Single Doors (Non-fire-rated) Hollow Metal

ii. 8'0 x 8'0 Pairs Hollow Metal

B. UL –ANSI/ICC 500 certified for F5 Tornado applications.

These products are listed with Steelcraft PW14 Series door for Tornado Listings.

### Product detail

Control Assembly



Top Rod Assembly



Bottom Rod Assembly

