

10

LHR LATCH APPLICATION SHOWN RHR OPPOSITE

CL DOOR & STRIKE

REINFORCE FOR STRIKE ATTACHMENT AS REQUIRED

CL STRIKE

SUGGESTED CUTOUT

$1\frac{7}{16}$ "
MIN. CLEARANCE

1" DIA
MIN. CLEARANCE

#12-24 TAP
2 HOLES

$2\frac{3}{8}$ "
MIN. CLEARANCE

$2\frac{3}{8}$ "
MIN. CLEARANCE

$\frac{1}{8}$ "

RHR DOOR SHOWN

SEE SHEET #2 FOR APPLICATION SCHEDULE

CL OF DOOR

$1\frac{3}{4}$ "

$\frac{7}{8}$ "

6" LONG LEAD WIRES
1/2" DIA. MIN.
WIRING ACCESS

3"

$1\frac{15}{16}$ "

$2\frac{5}{8}$ "

$1\frac{1}{16}$ "

$3\frac{1}{2}$ "

CL LATCH BOLT & STRIKE

6"

$3\frac{7}{8}$ "

$5\frac{1}{4}$ "

$3\frac{7}{8}$ "

MINIMUM CLEARANCE

$\frac{5}{8}$ "

$1\frac{1}{4}$ "

$\frac{1}{4}$ "

$1\frac{1}{4}$ "

REPLACES 3091/92 STRIKE

6223 ELECTRIC STRIKE
DOUBLE DOOR-CLOSED BACK APPLICATION



NOTE: SEE MASTER SHEET NO. 10001 FOR SUGGESTED REINFORCING.

TEMPLATE NUMBER: 30225_10SHT1

DATE: 07-30-02

6223 ELECTRIC STRIKE
 DOUBLE DOOR CLOSED BACK APPLICATION
 MORTISE/CYLINDRICAL APPLICATION SCHEDULE

PRODUCT MANUFACTURER	PRODUCT APPLICATION	THROW
VON DUPRIN	7500 MORTISE	3/4"
ADAMS RITE	4510 MORTISE	1/2"
ADAMS RITE	4710 MORTISE	5/8"
BALDWIN	6000 MORTISE	3/4"
BEST	24H, 30 SERIES MORTISE	3/4"
CORBIN/RUSSWIN	ML2200 SERIES MORTISE	3/4"
FALCON	M2300, M2500, M2600	3/4"
FALCON	M3300, M3500, M3600	5/8"
MONARCH	18-M MORTISE	3/4"
PRECISION	MORTISE	3/4"
SARGENT	7800/8200 MORTISE	3/4"
SARGENT	6500/8100 MORTISE	3/4"
SARGENT	900 MORTISE LOCK	3/4"
SCHLAGE	L9000 MORTISE	3/4"
YALE	8600 MORTISE	5/8"
YALE	8700 MORTISE	3/4"
BALDWIN	CYLINDRICAL	1/2"-3/4"
BEST	CYLINDRICAL	3/8"-3/4"
CORBIN	CYLINDRICAL	1/2"-3/4"
FALCON	CYLINDRICAL	1/2"-3/4"
RUSSWIN	CYLINDRICAL	1/2"-3/4"
SARGENT	CYLINDRICAL	1/2"-3/4"
SCHLAGE	CYLINDRICAL	3/8"-3/4"
YALE	CYLINDRICAL	1/2"-3/4"

NOTES:

1. DEADLATCH NOT GUARANTEED ON CYLINDRICAL APPLICATIONS.
2. MONITORING COULD BE AFFECTED BY DOOR/FRAME PREPARATION.
3. SIGNAL TRIPPER FUNCTION WITH 3/8" THROW BOLTS IS NOT RECOMMENDED.
4. NO DEADBOLT ACTION AVAILABLE FOR MORTISE APPLICATIONS.

REPLACES:

VON DUPRIN 3091/3092 ELECTRIC STRIKE

6223 ELECTRIC STRIKE
 DOUBLE DOOR-CLOSED BACK APPLICATION



NOTE: SEE MASTER SHEET NO. 10001 FOR SUGGESTED REINFORCING.

TEMPLATE NUMBER: 30225_10SHT2

DATE: 07-30-02