



OUTSIDE
FACE OF
LOCK STILE

INSIDE
FACE OF
LOCK STILE

FOR CUTOUT ON INSIDE FACE OF DOOR SEE DEVICE TEMPLATE	DEVICE APPLICATION SCHEDULE
	33A/35A RIM DEVICE
	3327A/3527A VERTICAL ROD DEVICE
	33/3527A-F VERTICAL ROD DEVICE
	3347A/3547A VERTICAL ROD DEVICE
	3348A/3548A VERTICAL ROD DEVICE
	33/3547A-F VERTICAL ROD DEVICE
33/3548A-F VERTICAL ROD DEVICE	

NOTES: SEE MASTER SHEET NO. 10001 FOR SUGGESTED REINFORCING.

TEMPLATE NUMBER: 40080_0

DATE: 06-27-03

360T, 360L, 360T-BE & 360L-BE CONTROL



LHR SHOWN
RHR OPPOSITE

CORRESPONDS TO CENTER
LINE OF DEVICE ON
DEVICE TEMPLATE

LINE X-X CORRESPONDS TO
LINE X-X ON DEVICE TEMPLATE

1 5/8" DIA CLEARANCE REQUIRED ON
INTERNAL LOCK STILE FEATURES FOR
ROTATION OF MORTISE CYLINDER CAM
IN AREA SHOWN BELOW. OMIT FOR "BE".

11/16" R
2 PLACES

OMIT SLOT
FOR "BE"
FUNCTION

11/16" DIA
FOR "BE"
FUNCTION

1 1/2" DIA
2 HOLES

5/16" DIA
2 HOLES

1/4"
2 1/16"
6 1/4"
3 1/8"

9/16"
1/4"